



CONCRETE HOSE

Grout & Plaster Hose

Application:

Mandrel built mandrel built delivery hose for plaster, concrete, slurry and abrasive materials with small granulometry. Suitable for plaster sprayers.

Tube:

Black smooth conductive rubber, abrasion resistant.

Reinforcement:

High tensile textile plies.

Cover:

Black, smooth rubber, weather and abrasion resistant. Fabric impression.

Working Pressure:

600 PSI, 40 bar

Nominal Burst Pressure:

1800 PSI, 120 bar



Temperature:

-40°F/+158°F (-40°C /+70°C)

Marking:

 PARAGON



 PART NO.	 Inner Diameter		 Outside Diameter		 Weight		 Max. L
	Inch	mm	Inch	mm	Lbs./Ft	Kg/m	ft/m
GRH-050-600	1/2	12.7	0.98	25	0.4	0.60	61/200
GRH-075-600	3/4	19.0	1.22	31	0.7	1.04	61/200
GRH-100-600	1	25.4	1.49	38	1.0	1.49	61/200
GRH-125-600	1 1/4	31.8	1.88	48	1.6	2.38	61/200
GRH-150-600	1 1/2	38.1	2.12	54	1.8	2.68	61/200
GRH-200-600	2	51	2.63	67	2.5	3.72	61/200
GRH-250-600	2 1/2	63	3.14	80	3.6	5.36	61/200
GRH-300-600	3	76	3.86	98	5.1	7.59	61/200
GRH-400-600	4	102	5.11	130	8.6	12.80	61/200